

95シリーズ  
 スタンダードサーモジュール  
 (高信頼性品・200℃瞬間耐熱) **鉛フリー**  
 ※推奨使用最高温度は135℃

品番	I <sub>max</sub> (A)	V <sub>max</sub> (V)	ΔT <sub>max</sub> (°C)	Q <sub>cmax</sub> (W)	外形寸法 (mm)			
					W1	L1	L2	T
9501/017/030B	3.0	2.3	72	3.8	11.5	11.5	-	3.18
9501/023/030B	3.0	3.2	72	5.2	7.39	22.4	-	3.18
9501/031/030B	3.0	4.3	72	7.0	15.1	15.1	-	3.18
9501/071/030B	3.0	9.8	72	16	22.4	22.4	-	3.18
9501/127/030B	3.0	17.5	72	29	29.7	29.7	-	3.94
9501/128/030B	3.0	17.6	72	29	29.7	29.7	34.0	3.94
9501/017/040B	4.0	2.3	72	5.1	11.5	11.5	-	3.18
9500/017/040B	4.0	2.3	72	5.1	15.1	15.1	-	4.16
9501/023/040B	4.0	3.2	72	6.9	7.39	22.4	-	3.18
9501/031/040B	4.0	4.3	72	9.3	15.1	15.1	-	3.18
9500/031/040B	4.0	4.3	72	9.3	20.0	20.0	-	4.16
9500/035/040B	4.0	4.8	72	10	15.1	29.8	-	4.16
9501/063/040B	4.0	8.7	72	18	20.1	39.7	-	4.16
9501/071/040B	4.0	9.8	72	21	22.4	22.4	-	3.18
9500/071/040B	4.0	9.8	72	21	29.8	29.8	-	4.16
9501/127/040B	4.0	17.5	72	38	29.7	29.7	-	3.94
9500/127/040B	4.0	17.5	72	38	39.7	39.7	-	4.16
9501/128/040B	4.0	17.6	72	38	29.7	29.7	34.0	3.94
9500/128/040B	4.0	17.6	72	38	39.7	39.7	42.8	4.16
9500/017/060B	6.0	2.3	72	7.6	15.1	15.1	-	4.16
9500/031/060B	6.0	4.3	72	14	20.0	20.0	-	4.16
9500/035/060B	6.0	4.8	72	16	15.1	29.8	-	4.16
9500/071/060B	6.0	9.8	72	32	29.8	29.8	-	4.16
9501/127/060B	6.0	17.5	72	57	29.7	29.7	-	3.61
9500/127/060B	6.0	17.5	72	57	39.7	39.7	-	4.16
9500/128/060B	6.0	17.6	72	57	39.7	39.7	42.8	4.16
9500/017/085B	8.5	2.3	72	11	15.1	15.1	-	3.94
9500/031/085B	8.5	4.3	72	20	20.0	20.0	-	3.94
9500/035/085B	8.5	4.8	72	22	15.1	29.8	-	3.94
9500/063/085B	8.5	8.7	72	40	39.7	39.7	-	3.94
9500/071/085B	8.5	9.8	72	45	29.8	29.8	-	3.94
9500/127/085B	8.5	17.5	72	80	39.7	39.7	-	3.94
9500/128/085B	8.5	17.6	72	80	39.7	39.7	42.8	3.94
9500/031/090B	9.0	4.3	72	22	29.8	29.8	-	4.60
9500/071/090B	9.0	9.8	72	47	29.8	29.8	-	3.94
9500/097/090B	9.0	13.3	72	65	29.8	29.8	-	3.55
9501/063/100B	10.0	8.7	72	47	20.1	39.7	-	3.64
9500/127/100B	10.0	17.5	72	95	39.7	39.7	-	3.64
9504/071/120B	12.0	9.8	72	63	40.1	40.1	-	4.65
9504/017/150B	15.0	2.3	72	19	22.0	22.0	-	4.65
9500/031/150B	15.0	4.3	72	35	29.8	29.8	-	4.60
9504/071/150B	15.0	9.8	72	79	40.1	40.1	-	4.65
9504/031/240B	24.0	4.3	72	55	39.7	39.7	-	4.62
9506/031/400B	40.0	4.3	72	92	55.0	55.0	-	4.85