

## 95シリーズ

### ハイパワーサーモモジュール

(高信頼性品・200°C瞬間耐熱) **鉛フリー**

※推奨使用最高温度は135°C

品番	I <sub>max</sub> (A)	V <sub>max</sub> (V)	ΔT <sub>max</sub> (°C)	Q <sub>cmax</sub> (W)	外形寸法 (mm)			
					W1	L1	L2	T
9500/241/060B	6.0	33.1	72	108	55.0	55.0	-	4.16
9500/241/085B	8.5	33.1	72	153	55.0	55.0	-	3.94
9500/391/085B	8.5	53.8	72	248	55.0	55.0	-	3.35
9500/199/100B	10.0	27.4	72	148	40.0	40.0	-	3.35
9500/241/100B	10.0	33.1	72	180	55.0	55.0	-	3.64
9500/337/100B	10.0	46.4	72	252	55.0	55.0	-	3.35
9500/127/120B	12.0	17.5	72	114	39.7	39.7	-	3.45
9505/127/150B	15.0	17.5	72	142	39.7	39.7	-	3.45
9500/131/150B	15.0	18.0	72	147	30.0	60.0	-	3.45
9501/242/160B	16.0	33.3	72	289	55.0	55.0	58.0	3.45
9506/031/600B	60.0	4.3	72	139	55.0	55.0	-	4.85